

---

# StorEdge<sup>®</sup> Three Phase Inverter

SE5K-RWS / SE7K-RWS / SE8K-RWS / SE10K-RWS



STOREDGE<sup>®</sup>

## Ideal solution for three phase installations with battery storage

- Simple installation with single inverter for managing both PV production and battery storage
- More energy using DC-coupled solution architecture that stores PV power directly to the battery without AC conversion losses
- Quick and easy inverter commissioning directly from a smartphone using the SolarEdge SetApp
- Designed to eliminate high voltage during installation, maintenance or firefighting for enhanced safety
- Built-in module-level monitoring and full visibility of battery status, PV production, and self-consumption data
- Allows connection of low voltage 48V batteries from multiple battery vendors to provide greater flexibility

# / StorEdge<sup>®</sup> Three Phase Inverter

## SE5K-RWS / SE7K-RWS / SE8K-RWS / SE10K-RWS

	SE5K-RWS	SE7K-RWS	SE8K-RWS	SE10K-RWS	
Applicable for inverters with part number	SEXK-XXS48XXXX				
<b>OUTPUT</b>					
Rated AC Power Output	5000	7000	8000	10000	VA
Maximum AC Power Output	5000	7000	8000	10000	VA
AC Output Voltage — Line to Line / Line to Neutral (Nominal)	380/220 ; 400/230				Vac
AC Output Voltage — Line to Neutral Range	184 - 264.5				Vac
AC Frequency	50/60 ± 5				Hz
Maximum Continuous Output Current (per Phase)	8	11.5	13	16	A
Residual Current Detector / Residual Current Step Detector	300 / 30				mA
Grids Supported — Three Phase	3 / N / PE (WYE with Neutral)				
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes				
<b>INPUT PV</b>					
Maximum DC Power (Module STC)	6750	9450	10800	13500	W
Transformer-less, Ungrounded	Yes				
Maximum Input Voltage	900				Vdc
Nominal DC Input Voltage	750				Vdc
Maximum Input Current	8.5	12	13.5	16.5	Adc
Reverse-Polarity Protection	Yes				
Ground-Fault Isolation Detection	700kΩ Sensitivity				
Maximum Inverter Efficiency	98				%
European Weighted Efficiency	97.3	97.4	97.6		%
Nighttime Power Consumption	< 2.5				W
<b>INPUT BATTERY</b>					
Maximum DC Power	5000				W
Input Voltage Range	40- 62				Vdc
Maximum Continuous Input Current	130				Adc
Battery Communication	CAN, RS485 (optional)				
<b>ADDITIONAL FEATURES</b>					
Supported Communication Interfaces	2 x RS485, Ethernet, Zigbee communications for Smart Energy <sup>(1)</sup> , Wi-Fi <sup>(2)</sup> , Built-in cellular (optional)				
<b>STANDARD COMPLIANCE</b>					
Safety	IEC-62109				
Grid Connection Standards <sup>(3)</sup>	VDE 0126-1-1, VDE-AR-N-4105, G98 / G99				
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12				
RoHS	Yes				
<b>INSTALLATION SPECIFICATIONS</b>					
AC Output – Cable Gland Diameter	15 - 21				mm
Battery DC – Cable Gland Diameter	2 x 8-11				mm
PV DC Input	2 x MC4 pair				
Dimensions (HxWxD)	853 x 316 x 193				mm
Weight	37				kg
Operating Temperature Range	-40 - +60				°C
Cooling	Internal and external fans				
Noise	< 50				dBA
Protection Rating	IP65 — Outdoor and Indoor				
Mounting	Bracket provided				

<sup>(1)</sup> For more information refer to: <https://www.solaredge.com/sites/default/files/se-zigbee-plug-in-wireless-communication-for-setapp-datasheet.pdf>

<sup>(2)</sup> Wi-Fi connectivity requires an external antenna. For more information refer to: <https://www.solaredge.com/sites/default/files/se-wifi-zigbee-antenna-datasheet.pdf>

<sup>(3)</sup> For all standards refer to Certifications category in Downloads page: <http://www.solaredge.com/groups/support/downloads>